

PBB Command Reference

Command Hierarchies

- Global Commands on page 1155
- SAP Commands on page 1157
- Mesh SDP Commands on page 1157
- Spoke SDP Commands on page 1157
- Show Commands on page 1158
- Clear Commands on page 1159
- Debug Commands on page 1159

Global Commands

```

config
  — service
    — [no] vpls service-id [customer customer-id] [vpn vpn-id] [m-vpls] [b-vpls|i-vpls] [create]
      — [no] spb instance [fid value] [create]
        — [no] shutdown
        — level level-number
          — bridge-priority value
          — ect-algorithm name fid-range fid-range
          — forwarding-tree-topology[st|spf]
        — lsp-lifetime seconds
        — no lsp-lifetime
        — lsp-wait lsp-wait [lsp-initial-wait [lsp-second-wait]]
        — overload [timeout seconds]
        — no overload
        — overload-on-boot [timeout seconds]
        — no overload-on-boot
        — [no] spf-wait spf-wait [spf-initial-wait [spf-second-wait]]
    — spbm-control-vpls mgmt vpls svc id fid val
    — no spbm-control-vpls
    — mrp
      — [no] attribute-table-high-wmark high-water-mark
      — [no] attribute-table-low-wmark low-water-mark
      — [no] attribute-table-size max-attributes
      — flood-time flood-time
      — no flood-time
      — [no] shutdown
    — mrp
      — [no] mrp-policy policy-name
        — description description-string
        — no description
        — scope {exclusive | template}
        — no scope
        — default-action {block | allow}

```

```

    — [no] entry entry-id
        — description description-string
        — no description
        — [no] match
            — [no] isid value | from value to higher-value
            — action {block | allow | end-station}
            — no action
    — copy mrp-policy source-name to dest-name
        — renum old-entry-id to new-entry-id

config
    — service
        — ppb
            — mac-name name ieee-address
            — no mac-name
            — source-bmac ieee-address
            — no source-bmac

config
    — service
        — [no] vpls service-id [customer customer-id] [b-vpls] [create]
            — ppb
                — [no] force-qtag-forwarding
                — source-bmac ieee-address
                — no source-bmac
                — [no] use-sap-bmac
                — mac-notification
                    — [no] count value
                    — [no] interval value
                    — renotify value
                    — no renotify

config
    — service
        — [no] vpls service-id [customer customer-id] [i-vpls] [create]
            — ppb
                — backbone-vpls service-id [isid isid]
                — no backbone-vpls
                    — igmp-snooping
                        — [no] mrouter-dest mac-name
                        — [no] sap sap-id
                            — igmp-snooping
                                — [no] mrouter-port
                        — [no] sdp sdp-id:vc-id
                            — igmp-snooping
                                — [no] mrouter-port
                        — [no] stp
                    — [no] force-qtag-forwarding
                    — [no] send-bvpls-flush {[all-from-me] | [all-but-mine]}

config
    — service

```

- **epipe** *service-id* [**customer** *customer-id*] [**create**] [**vpn** *vpn-id*] [**vc-switching**]
- **no epipe** *service-id*
 - **ppb**
 - [no] **force-qtag-forwarding**

SAP Commands

```

config
  — service
    — [no] vpls service-id [customer customer-id] [vpn vpn-id] [mvpls] [b-vpls|i-vpls] [create]
      — sap sap-id [split-horizon-group group-name] [create] [capture-sap]
      — no sap sap-id
        — mrp
          — [no] join-time value
          — [no] leave-all-time value
          — [no] leave-time value
          — [no] mrp-policy policy-name
          — [no] periodic-time value
          — [no] periodic-timer
        — [no] spb create
          — [no] shutdown
          — lsp-pacing-interval milliseconds
          — no lsp-pacing-interval
          — retransmit-interval seconds
          — no retransmit-interval
          — metric value
          — no metric
            — hello-interval seconds
            — no hello-interval
            — hello-multiplier multiplier
            — no hello-multiplier

```

Mesh SDP Commands

```

config
  — service
    — [no] vpls service-id [customer customer-id] [vpn vpn-id] [mvpls] [b-vpls|i-vpls] [create]
      — mesh-sdp sdp-id[:vc-id] [vc-type {ether | vlan}]
      — no mesh-sdp sdp-id[:vc-id]
        — mrp
          — [no] join-time value
          — [no] leave-all-time value
          — [no] leave-time value
          — [no] mrp-policy policy-name
          — [no] periodic-time value
          — [no] periodic-timer

```

Spoke SDP Commands

```

config
  — service
    — [no] vpls service-id [customer customer-id] [vpn vpn-id] [mvpls] [b-vpls|i-vpls] [create]

```

- **spoke-sdp** *sdp-id[:vc-id]* [vc-type {ether | vlan}] [split-horizon-group *group-name*]
- **no spoke-sdp** *sdp-id[:vc-id]*
 - **mrp**
 - [no] **join-time** *value*
 - [no] **leave-all-time** *value*
 - [no] **leave-time** *value*
 - [no] **mrp-policy** *policy-name*
 - [no] **periodic-time** *value*
 - [no] **periodic-timer**
 - [no] **spb create**
 - [no] **shutdown**
 - **lsp-pacing-interval** *milliseconds*
 - **no lsp-pacing-interval**
 - **retransmit-interval** *seconds*
 - **no retransmit-interval**
 - **metric** *value*
 - **no metric**
 - **hello-interval** *seconds*
 - **no hello-interval**
 - **hello-multiplier** *multiplier*
 - **no hello-multiplier**

Show Commands

```
show
  — eth-cfm
    — association [ma-index] [detail]
    — cfm-stack-table [port port-id [vlan vlan-id]] | sdp sdp-id[:vc-id] [level 0..7] [direction up|down]
    — domain [md-index] [association ma-index | all-associations [detail]]]
    — mep mep-id domain md-index association ma-index [loopback] [linktrace]
  — service
    — id service-id
      — i-vpls
      — mrp-policy mac [ieee-address]
      — mrp
      — spb
        — adjacency [detail]
        — base
        — database
        — fate-sharing
        — fid [fid] fate-sharing
        — fid [fid] user-service
        — fid [fid] fdb
        — fid [fid] mfib [group-mac <ieee-address>]
        — fid [fid] mfib [isid <isid>]
        — hostname
        — interface
        — mfib [detail]
        — routes
        — spf
        — spf-log
        — status
      — mrp-policy [mrp-policy]
      — mrp-policy mrp-policy [association]
```

- **mrp-policy** *mrp-policy* [**entry** *entry-id*]
- **ppb**
 - **base**
 - **mac-name** [**detail**]

Clear Commands

```
clear
  — service
    — statistics
      — id service-id
        — counters
        — mesh-sdp sdp-id[:vc-id] {all | counters | stp | mrp}
        — mrp
        — spoke-sdp sdp-id[:vc-id] {all | counters | stp | mrp}
        — stp
        — spb
          — adjacency [detail]
          — database
          — spf-log
          — status
      — sap sap-id {all | counters | stp | l2pt | mrp}
```

Debug Commands

```
debug
  — service
    — id service-id
      — [no] mrp
        — all-events
        — [no] applicant-sm
        — [no] leave-all-sm
        — [no] mmrp-mac ieee-address
        — [no] mr pdu
        — [no] periodic-sm
        — [no] registrant-sm
        — [no] sap sap-id
        — [no] sdp sdp-id:vc-id
        — [no] spb
          — [no] adjacency {sap sap-id | spoke-sdp sdp-id:vc-id | nbr-system-id}
          — [no] interface { sap <sap-id> | spoke-sdp <sdp-id:vc-id> }
          — [no] l2db
          — [no] lsdb {system-id | lsp-id }
          — [no] packet { p top-hello l1-hello l1-psnp l1-csnp l1-lsp } detail
          — [no] spf { system-id }
```

