

Common CLI Command Descriptions

In This Chapter

This chapter provides CLI syntax and command descriptions for SAP and port commands.

Topics in this chapter include:

- [SAP Syntax on page 640](#)
- [Port Syntax on page 642](#)

Common Service Commands

sap

Syntax [no] sap *sap-id*

Syntax [no] sap *sap-id*

Description This command specifies the physical port identifier portion of the SAP definition.

Parameters *sap-id* — Specifies the physical port identifier portion of the SAP definition.

The *sap-id* can be configured in one of the following formats:

Type	Syntax	Example
port-id	<i>slot/mda/port[.channel]</i>	1/1/5
null	<i>[port-id bundle-id] bpgrp-id lag-id aps-id</i>	<i>port-id:</i> 1/1/3 <i>bundle-id:</i> bundle-ppp-1/1.1 <i>bpgrp-id:</i> bpgrp-ima-1 <i>lag-id:</i> lag-3 <i>aps-id:</i> aps-1
dot1q	<i>[port-id bundle-id] bpgrp-id lag-id aps-id]:qtag1</i>	<i>port-id:</i> qtag1: 1/1/3:100 <i>bundle-id:</i> bundle-ppp-1/1.1 <i>bpgrp-id:</i> bpgrp-ima-1 <i>lag-id:</i> qtag1:lag-3:102 <i>aps-id:</i> qtag1: aps-1:27
qinq	<i>[port-id bpgrp-id lag-id]:qtag1.qtag2</i>	<i>port-id:</i> qtag1.qtag2: 1/1/3:100.10 <i>bpgrp-id:</i> bpgrp-ima-1 <i>lag-id:</i> qtag1.qtag2: lag-10:
atm	<i>[port-id aps-id bundle-id bpgrp-id][:vpi/vci vpi vpi1.vpi2]</i>	<i>port-id:</i> 1/1/1 <i>aps-id:</i> aps-1 <i>bundle-id:</i> bundle-ima-1/1.1 bundle-ppp-1/1.1 <i>bpgrp-id:</i> bpgrp-ima-1 <i>vpi/vci:</i> 16/26 <i>vpi:</i> 16 <i>vpi1.vpi2:</i> 16.200
frame-relay	<i>[port-id aps-id]:dlci</i>	<i>port-id:</i> 1/1/1:100 <i>bundle-id:</i> bundle-fr-3/1.1:100 <i>aps-id:</i> aps-1 <i>dlci:</i> 16
cisco-hdlc	<i>slot/mda/port.channel</i>	<i>port-id:</i> 1/1/3.1

7750 SR:

Values:	<i>sap-id</i>	null [port-id bundle-id bpgrp-id lag-id aps-id] dot1q [port-id bundle-id bpgrp-id lag-id aps-id]:qtag1 qinq [port-id bundle-id bpgrp-id lag-id]:qtag1.qtag2 atm [port-id aps-id][:vpi/vci vpi vpi1.vpi2] frame [port-id aps-id]:dlci cisco-hdlc slot/mda/port.channel cem slot/mda/port.channel ima-grp [bundle-id][:vpi/vci vpi vpi1.vpi2] port-id slot/mda/port[.channel] bundle-id bundle-type-slot/mda.bundle-num bundle keyword type ima, fr, ppp bundle-num 1 — 336 bpgrp-id bpgrp-type-bpgrp-num bpgrp keyword type ima, ppp bpgrp-num 1 — 2000 aps-id aps-group-id[.channel] aps keyword group-id 1 — 64 ccag-id ccag-id.path-id[cc-type]:cc-id ccag keyword id 1 — 8 path-id a, b cc-type .sap-net, .net-sap cc-id 0 — 4094 eth-tunnel eth-tunnel-id[:eth-tun-sap-id] id 1 — 1024 eth-tun-sap-id 0 — 4094 lag-id lag-id lag keyword id 1 — 800 qtag1 0 — 4094 qtag2 *, 0 — 4094 vpi NNI: 0 — 4095 UNI: 0 — 255 vci 1, 2, 5 — 65535 dlci 16 — 1022 ipsec-id ipsec-id.[private public]:tag ipsec keyword id 1 — 4 tag 0 — 4094
----------------	---------------	----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------

port

Syntax `port port-id`

Description This command specifies a port identifier.

Parameters *port-id* — The *port-id* can be configured in one of the following formats.

Values	port-id	
	slot/mda/port[.channel]	
	bundle-id	bundle-type-slot/mda.bundle-num
	bundle	keyword
	type	ima ppp
	bundle-num1	1 — 256
	bpgrp-id	bpgrp-type-bpgrp-num
	bpgrp	keyword
	type	ima, ppp
	bpgrp-num1	1 — 256
	aps-id	aps-group-id[.channel]
	aps	keyword
	group-id	1 — 64
	ccag-id	ccag-id.<path-id>[cc-type]
	ccag	keyword
	id	1 — 8
	path-id	a, b
	cc-type	[.sap-net .net-sap]
	lag-id	lag-id
	lag	keyword
	id	1— 200